



When technological Innovation Combines with Simplicity

A new wireless and ultra efficient perimeter alarm system created by Firstinnov'

The flexibility of Primaprotect enables it to adapt to all shapes of swimming pools. Composed of a master pole with an integrated siren and from 1 to 5 slave poles depending on the configuration of the pool. Primaprotect is the first wireless perimeter alarm system. It is equipped with infrared cells.

Goodbye ugly cables and complicated wirings to power or connect the poles. Primaprotect is easy to install and easy to maintain.

Its diagnostic function enables to monitor the operation state of the system and to detect any dysfunction.

Evolutionary alarm, Primaprotect offers a complete range of accessories. Safety bracelet- Remote control- Digicode- Wireless siren- Gate sensor.

Optional safety bracelet for a double and continuous protection

A particularly innovating concept of a high efficiency.

This safety bracelet* is placed around the child's wrist. So light and ergonomic that your child will forget about it. Once locked only an adult could take it off.

In case of a fall into the water, the bracelet will transmit a radio frequency signal to the central unit within less than a second and the alarm will go off.

Its efficiency is permanent because the bracelet will protect your child even when the perimeter alarm is disarmed while swimming.

Primaprotect conforms with the French standard NF P 90-307

* Bracelet incompatible with salted water.



Prima protect

A flexible alarm system

Around the "Master pole" will gravitate from 1 to 5 "Slave poles" for a maximum security.

For instance: To protect 1 or 2 sides of a traditional pool, 1 Master pole and 1 or 2 Slave poles will be necessary.

Master Pole

Ref : DSP80-3x3



Slave Pole

Ref : DSP80-3x2




The main protection KIT

Protection 3 or 4 sides of the swimming pool

The 3 or 4 sides protection kit DSP80-F4 is composed of:

- 1 master pole reference DSP80-3X3 equipped with 4 infrared cells, 1 integrated siren and LEDs.
- 3 slaves poles reference DSP80-3X2 equipped with 4 infrared cells.



A complete range of accessories

Ref : DSP10-1W

Safety bracelet*



*Bracelet incompatible with salted water.

Ref : DSP20-1R

Remote control



Ref : DSP10-1H

Gate sensor



Ref : DSP40-1R1

Digicode



Réf : DSP20-3K

Wireless additional siren



PRIMAPROTECT MAIN TECHNICAL CHARACTERISTICS

Height of the poles	67 cm
Height of the zone of protection	20 cm and 45 cm
Power supply of the pole	3 V Battery pack
Power supply of the master pole	9 V Battery pack
Audible alarm	100 db at 1 m
Autonomy of the batteries	1 to 2 years
Maximum distance between two poles	20 m
Angle of alignments of the sensors	125° horizontal and ±10° vertical
Maximum number of poles	6
Warranty	2 years

first innov
● The Comfort of Electronic Safety